



Andor CB2

CXP Features Reference

Andor CB2 CXP Features Reference



TABLE

1.	DeviceControl.....	7
1.1.	DeviceScanType.....	7
1.2.	DeviceVendorName	7
1.3.	DeviceModelName.....	7
1.4.	DeviceFamilyName.....	7
1.5.	DeviceManufacturerInfo	8
1.6.	DeviceVersion.....	8
1.7.	DeviceFirmwareVersion	8
1.8.	DeviceFPGAVersion	9
1.9.	DeviceSerialNumber	9
1.10.	DeviceUserID.....	9
1.11.	DeviceReset.....	9
1.12.	DeviceShutdown.....	10
1.13.	DeviceIndicatorMode.....	10
1.14.	DeviceTemperatureSelector	10
1.15.	DeviceTemperature[DeviceTemperatureSelector]	11
1.16.	DeviceTecSelector.....	11
1.17.	DeviceTecVoltage[DeviceTecSelector]	11
1.18.	DeviceTecCurrent[DeviceTecSelector]	12
1.19.	DeviceTecPower[DeviceTecSelector]	12
1.20.	DeviceFanMode	12
1.21.	DeviceFanSpeed	12
1.22.	DeviceCoolingEnable	13
1.23.	DeviceCoolingSetpoint	13
1.24.	DeviceStatus	13
1.25.	DeviceStatusDetailed	13
2.	DeviceMaintenance.....	14
2.1.	DeviceDate	14
2.2.	TotalUptime	14
2.3.	FirmwareUpdateUri	14
2.4.	FirmwareUpdateExecute	14
2.5.	FirmwareUpdateAbort	14
2.6.	FirmwareUpdateStatusRefresh	15
2.7.	FirmwareUpdateStatus	15
2.8.	LogHistoryDepth	16
2.9.	LogCollect	16
2.10.	LogCollectAbort	16

2.11.	LogCollectStatus.....	16
2.12.	LogCollectStatusRefresh.....	17
2.13.	LogServe.....	17
2.14.	LogServeAbort.....	17
2.15.	LogServeUri.....	18
3.	NonUniformityCorrectionControl.....	18
3.1.	NucMode.....	18
3.2.	BuildBiasExecute.....	18
3.3.	BuildFlatExecute.....	19
3.4.	BuildNucNbImages	19
3.5.	BuildNucAbort.....	19
3.6.	BuildNucStatusRefresh	19
3.7.	BuildNucStatus	20
3.8.	BuildNucDuration.....	20
3.9.	AduOffset.....	20
4.	ImageProcessingControl	21
4.1.	MedianFilterThresholdEnable	21
4.2.	MedianFilterThreshold.....	21
4.3.	MedianFilterSaturationEnable	21
5.	DebugEthernet	21
5.1.	CurrentIPAddress	21
5.2.	CurrentSubnetMask	22
5.3.	IPMode	22
5.4.	IPReconfigure	22
5.5.	StaticIPAddress	22
5.6.	StaticSubnetMask.....	23
5.7.	StaticDefaultGateway.....	23
5.8.	StaticDomainNameServer.....	23
5.9.	StaticAlternateDomainNameServer	23
5.10.	IPRestoreDefault.....	24
6.	ImageFormatControl	24
6.1.	SensorWidth.....	24
6.2.	SensorHeight.....	24
6.3.	SensorPixelWidth	25
6.4.	SensorPixelHeight.....	25
6.5.	SensorName	25
6.6.	SensorShutterMode	26
6.7.	WidthMax.....	26
6.8.	HeightMax	26

6.9.	RegionSelector.....	27
6.10.	RegionMode.....	27
6.11.	RegionDestination[RegionSelector]	27
6.12.	Width[RegionSelector].....	28
6.13.	Height[RegionSelector].....	28
6.14.	OffsetX[RegionSelector].....	28
6.15.	OffsetY[RegionSelector].....	29
6.16.	Sparse[RegionSelector].....	29
6.17.	SparseSelector[RegionSelector].....	29
6.18.	SparseWidth[RegionSelector][SparseSelector]	30
6.19.	SparseHeight[RegionSelector][SparseSelector]	31
6.20.	SparseOffsetX[RegionSelector][SparseSelector]	31
6.21.	SparseOffsetY[RegionSelector][SparseSelector]	31
6.22.	SparseMode[SparseSelector]	32
6.23.	BinningSelector	32
6.24.	BinningHorizontalMode[BinningSelector]	33
6.25.	BinningHorizontal[BinningSelector].....	33
6.26.	BinningVerticalMode[BinningSelector]	34
6.27.	BinningVertical[BinningSelector]	34
6.28.	ReverseX.....	35
6.29.	ReverseY.....	35
6.30.	PixelFormat.....	35
6.31.	HDRMode.....	36
6.32.	TestPattern.....	37
7.	AcquisitionControl.....	38
7.1.	AcquisitionMode.....	38
7.2.	AcquisitionStart.....	38
7.3.	AcquisitionStop.....	38
7.4.	AcquisitionStarted.....	39
7.5.	AcquisitionAbort	39
7.6.	AcquisitionBurstFrameCount	39
7.7.	AcquisitionFrameRate	39
7.8.	MaximumExternalAcquisitionFrameRate	40
7.9.	AcquisitionLineDelay.....	40
7.10.	TriggerSelector.....	40
7.11.	TriggerMode[TriggerSelector]	41
7.12.	TriggerSoftware[TriggerSelector]	41
7.13.	TriggerSource[TriggerSelector]	41
7.14.	TriggerActivation[TriggerSelector].....	42

7.15. TriggerOverlap[TriggerSelector].....	42
7.16. TriggerDelay[TriggerSelector].....	43
7.17. ExposureMode.....	43
7.18. ExposureTime.....	43
7.19. MinimumExternalExposureTime	44
7.20. GlowReduction.....	44
8. AnalogControl.....	44
8.1. GainSelector.....	44
8.2. Gain[GainSelector].....	45
8.3. BlackLevelSelector.....	45
8.4. BlackLevel[BlackLevelSelector].....	45
8.5. BlackLevelAuto[BlackLevelSelector].....	46
8.6. ConversionEfficiency	46
9. DigitalIOControl	47
9.1. LineSelector.....	47
9.2. LineMode[LineSelector].....	47
9.3. LineSource[LineSelector].....	47
10. UserSetControl.....	48
10.1. UserSetSelector.....	48
10.2. UserSetLoad.....	49
10.3. UserSetSave.....	49
10.4. UserSetDefault.....	49
11. FileAccessControl.....	50
11.1. FileSelector.....	50
11.2. FileOperationSelector[FileSelector].....	50
11.3. FileOperationExecute[FileOperationSelector]	51
11.4. FileOpenModel[FileSelector].....	51
11.5. FileAccessOffset[FileOperationSelector].....	52
11.6. FileAccessLength[FileOperationSelector].....	52
11.7. FileOperationStatus[FileOperationSelector].....	52
11.8. FileOperationResult[FileOperationSelector].....	52
11.9. FileSize[FileSelector].....	53
12. TransportLayerControl.....	53
12.1. TLParamsLocked.....	53
12.2. PayloadSize	53
13. CoaXPress.....	54
13.1. CxpLinkConfigurationStatus	54
13.2. CxpLinkConfigurationPreferred.....	55
13.3. CxpLinkConfiguration	55

13.4. CxpConnectionSelector	56
13.5. CxpConnectionTestMode[CxpConnectionSelectorReg].....	56
13.6. CxpConnectionTestErrorCount[CxpConnectionSelectorReg].....	57
13.7. CxpSendReceiveSelector.....	57
13.8. CxpConnectionTestPacketCount[CxpSendReceiveSelector].....	57
13.9. CxpErrorCounterSelector.....	58
13.10.CxpErrorCounterReset[CxpErrorCounterSelector].....	58
13.11.CxpErrorCounterValue[CxpErrorCounterSelector].....	59
13.12.CxpErrorCounterStatus[CxpErrorCounterSelector].....	59

1. DeviceControl

1.1. DeviceScanType

Scan type of the sensor of the device.

Feature	Value
Display Name	Device Scan Type
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RO
Visibility	Expert
Category	DeviceControl

Possible values	Description
Areascan	2D sensor.

1.2. DeviceVendorName

Name of the manufacturer of the device.

Feature	Value
Display Name	Device Vendor Name
Standard	GeniCam SFNC Version 2.5
Feature type	String
Access	RO
Visibility	Beginner
Category	DeviceControl

DeviceVendorName is set to "First Light Imaging" on C-BLUE cameras.

1.3. DeviceModelName

Model of the device.

Feature	Value
Display Name	Device Model Name
Standard	GeniCam SFNC Version 2.5
Feature type	String
Access	RO
Visibility	Beginner
Category	DeviceControl

DeviceModelName value varies according to the variant of the camera:

"C-BLUE 2 1.7 MP" for cameras equipped with a IMX425 sensor

"C-BLUE 2 0.5 MP" for cameras equipped with a IMX426 sensor

"C-BLUE 2 7.1 MP" for cameras equipped with a IMX420 sensor

"C-BLUE 2 24.5 MP" for cameras equipped with a IMX530 sensor

"C-BLUE 2 UV" for cameras equipped with a IMX487 sensor

1.4. DeviceFamilyName

Identifier of the product family of the device.

Feature	Value
Display Name	Device Family Name
Standard	GeniCam SFNC Version 2.5
Feature type	String
Access	RO
Visibility	Beginner
Category	DeviceControl

DeviceFamilyName is set to "C-BLUE".

1.5. DeviceManufacturerInfo

Manufacturer information about the device.

Feature	Value
Display Name	Device Manufacturer Info
Standard	GeniCam SFNC Version 2.5
Feature type	String
Access	RO
Visibility	Beginner
Category	DeviceControl

DeviceManufacturerInfo is set to "C-BLUE 2".

1.6. DeviceVersion

Version of the device.

Feature	Value
Display Name	Device Version
Standard	GeniCam SFNC Version 2.5
Feature type	String
Access	RO
Visibility	Beginner
Category	DeviceControl

1.7. DeviceFirmwareVersion

Version of the firmware in the device.

Feature	Value
Display Name	Device Firmware Version
Standard	GeniCam SFNC Version 2.5
Feature type	String
Access	RO
Visibility	Beginner
Category	DeviceControl

1.8. DeviceFPGAVersion

Version of the FPGA in the device.

Feature	Value
Display Name	Device FPGA Version
Standard	Custom
Feature type	String
Access	RO
Visibility	Expert
Category	DeviceControl

1.9. DeviceSerialNumber

Device's serial number. This string is a unique identifier of the device.

Feature	Value
Display Name	Device Serial Number
Standard	GeniCam SFNC Version 2.5
Feature type	String
Access	RO
Visibility	Expert
Category	DeviceControl

1.10. DeviceUserID

User-programmable device identifier.

Feature	Value
Display Name	Device User ID
Standard	GeniCam SFNC Version 2.5
Feature type	String
Access	RW
Visibility	Beginner
Category	DeviceControl

1.11. DeviceReset

Resets the device. After reset, the device must be rediscovered.

Feature	Value
Display Name	Device Reset
Standard	GeniCam SFNC Version 2.5
Feature type	Command
Access	WO
Visibility	Guru
Category	DeviceControl

1.12. DeviceShutdown

Turns the device off.

Feature	Value
Display Name	Device Shutdown
Standard	Custom
Feature type	Command
Access	WO
Visibility	Beginner
Category	DeviceControl

1.13. DeviceIndicatorMode

Controls the behavior of the indicators (such as LEDs) showing the status of the Device.

Feature	Value
Display Name	Device Indicator Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	DeviceControl

Possible values	Description
<i>Inactive</i>	Device's indicators are inactive (Off).
<i>Active</i>	Device's indicators are active showing their respective status.
<i>ErrorStatus</i>	Device's indicators are inactive unless an error occurs.
<i>CxpLedRed</i>	Sets CXP led color to red.
<i>CxpLedGreen</i>	Sets CXP led color to green.
<i>CxpLedBrightGreen</i>	Sets CXP led color to bright green.

1.14. DeviceTemperatureSelector

Selects the location within the device, where the temperature will be measured.

Feature	Value
Display Name	Device Temperature Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	DeviceControl
Selects	DeviceTemperature

Possible values	Description
<i>Sensor</i>	Temperature of the image sensor of the camera.
<i>CPU</i>	Temperature of the device's CPU.
<i>Power</i>	Temperature of the device's power module.
<i>Frontend</i>	Temperature of the device's frontend module.
<i>Heatsink</i>	Temperature of the device's heatsink.
<i>Case</i>	Temperature of the device's case.

1.15. DeviceTemperature[DeviceTemperatureSelector]

Device temperature in degrees Celsius (C). It is measured at the location selected by DeviceTemperatureSelector.

Feature	Value
Display Name	Device Temperature
Standard	GeniCam SFNC Version 2.5
Feature type	Float
Access	RO
Visibility	Expert
Unit	C
Category	DeviceControl

1.16. DeviceTecSelector

Selects the TEC module within the device, where voltage, current and power will be measured.

Feature	Value
Display Name	Device Tec Selector
Standard	Custom
Feature type	Enumeration
Access	RW
Visibility	Guru
Category	DeviceControl
Selects	DeviceTecVoltage DeviceTecCurrent DeviceTecPower

Possible values	Description
TEC1	Primary TEC.

1.17. DeviceTecVoltage[DeviceTecSelector]

Voltage applied to TEC in Volts (V). It is measured at the TEC selected by DeviceTecSelector.

Feature	Value
Display Name	Device TEC Voltage
Standard	Custom
Feature type	Float
Access	RO
Visibility	Guru
Unit	V
Category	DeviceControl

1.18. DeviceTecCurrent[DeviceTecSelector]

Current consumed by the TEC in Amperes (A). It is measured at the TEC selected by DeviceTecSelector.

Feature	Value
Display Name	Device TEC Current
Standard	Custom
Feature type	Float
Access	RO
Visibility	Guru
Unit	A
Category	DeviceControl

1.19. DeviceTecPower[DeviceTecSelector]

TEC power consumption in Watts (W). It is measured at the TEC selected by DeviceTecSelector.

Feature	Value
Display Name	Device TEC Power
Standard	Custom
Feature type	Float
Access	RO
Visibility	Guru
Unit	W
Category	DeviceControl

1.20. DeviceFanMode

Selects the mode of operation of the device fan.

Feature	Value
Display Name	Device Fan Mode
Standard	Custom
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	DeviceControl

Possible values	Description
<i>Automatic</i>	The fan speed is controlled by the camera.
<i>Manual</i>	The fan speed is controlled by the user using DeviceFanSpeed register.

1.21. DeviceFanSpeed

Selects the speed of the fan in manual mode.

Feature	Value
Display Name	Device Fan Speed
Standard	Custom
Feature type	Integer
Access	RW
Visibility	Expert
Category	DeviceControl

1.22. DeviceCoolingEnable

Controls if the sensor cooling is enabled.

Feature	Value
Display Name	Cooling Enable
Standard	Custom
Feature type	Boolean
Access	RW
Visibility	Beginner
Category	DeviceControl

The cooling of the sensor can only be enabled when the camera is powered using the provided power supply attached to the Lemo power connector.

1.23. DeviceCoolingSetpoint

Specifies the sensor temperature target in degree Celsius when cooling is enabled.

Feature	Value
Display Name	Cooling SetPoint
Standard	Custom
Feature type	Float
Access	RW
Visibility	Beginner
Unit	°C
Category	DeviceControl

1.24. DeviceStatus

Status of the device.

Feature	Value
Display Name	Device Status
Standard	Custom
Feature type	String
Access	RO
Visibility	Beginner
Category	DeviceControl

1.25. DeviceStatusDetailed

Detailed status of the device.

Feature	Value
Display Name	Detailed Status Device
Standard	Custom
Feature type	String
Access	RO
Visibility	Expert
Category	DeviceControl

2. Device Maintenance

2.1. DeviceDate

Controls the date of the camera. Format is YYYY-MM-DD HH:MM:SS

Feature	Value
Display Name	Date (UTC)
Standard	Custom
Feature type	String
Access	RW
Visibility	Guru
Category	DeviceMaintenance

2.2. TotalUptime

Specifies the total uptime of the camera.

Feature	Value
Display Name	Total Uptime
Standard	Custom
Feature type	String
Access	RO
Visibility	Guru
Category	DeviceMaintenance

2.3. FirmwareUpdateUri

Specifies location of firmware update (max 255 bytes).

Feature	Value
Display Name	Firmware Update location
Standard	Custom
Feature type	String
Access	RW
Visibility	Expert
Category	DeviceMaintenance

2.4. FirmwareUpdateExecute

Launches the firmware update procedure.

Feature	Value
Display Name	Launch firmware update
Standard	Custom
Feature type	Command
Access	WO
Visibility	Expert
Category	DeviceMaintenance
Affects	FirmwareUpdateStatus

2.5. FirmwareUpdateAbort

Aborts the firmware update procedure in progress.

Feature	Value
Display Name	Aborts firmware update in progress
Standard	Custom
Feature type	Command
Access	WO
Visibility	Expert
Category	DeviceMaintenance
Affects	FirmwareUpdateStatus

2.6. FirmwareUpdateStatusRefresh

Forces reload of firmware update status. This is only needed for implementation that do not handle IsSelfClearing properly.

Feature	Value
Display Name	Forces reload of firmware update status
Standard	Custom
Feature type	Command
Access	WO
Visibility	Expert
Category	DeviceMaintenance
Affects	FirmwareUpdateStatus

2.7. FirmwareUpdateStatus

Returns firmware update status.

Feature	Value
Display Name	Firmware update status
Standard	Custom
Feature type	Enumeration
Access	RO
Visibility	Expert
Category	DeviceMaintenance

Possible values	Description
<i>Idle</i>	No firmware update operation has been requested.
<i>InProgress</i>	Firmware update operation in progress.
<i>Done</i>	Last firmware update operation succeeded. Reboot the camera to apply new firmware configuration
<i>Failed</i>	Last firmware update operation failed.

2.8. LogHistoryDepth

Specifies the log history depth in days.

Feature	Value
Display Name	Log History Depth
Standard	Custom
Feature type	Integer
Access	RW
Visibility	Guru
Unit	days
Category	DeviceMaintenance

2.9. LogCollect

Collects the logs.

Feature	Value
Display Name	Log Collect
Standard	Custom
Feature type	Command
Access	WO
Visibility	Guru
Category	DeviceMaintenance
Affects	LogCollectStatus

2.10. LogCollectAbort

Aborts collecting of the logs.

Feature	Value
Display Name	Log Collect Abort
Standard	Custom
Feature type	Command
Access	WO
Visibility	Guru
Category	DeviceMaintenance
Affects	LogCollectStatus

2.11. LogCollectStatus

Returns log collect status.

Feature	Value
Display Name	Log Collect Status
Standard	Custom
Feature type	Enumeration
Access	RO
Visibility	Guru
Category	DeviceMaintenance

Possible values	Description
<i>Idle</i>	No log collect operation has been requested.
<i>InProgress</i>	Log collect operation in progress.
<i>Done</i>	Log collect succeeded. The logs can now be served.
<i>Failed</i>	Log collect failed.

2.12. LogCollectStatusRefresh

Forces reload of log collecting status. This is only needed for implementation that do not handle IsSelfClearing properly.

Feature	Value
Display Name	Forces reload of log collecting status.
Standard	Custom
Feature type	Command
Access	WO
Visibility	Guru
Category	DeviceMaintenance
Affects	LogCollectStatus

2.13. LogServe

Serves the logs previously collected.

Feature	Value
Display Name	LogServe
Standard	Custom
Feature type	Command
Access	WO
Visibility	Guru
Category	DeviceMaintenance
Affects	LogServeUri

2.14. LogServeAbort

Aborts serving of the logs.

Feature	Value
Display Name	LogServeAbort
Standard	Custom
Feature type	Command
Access	WO
Visibility	Guru
Category	DeviceMaintenance
Affects	LogServeUri

2.15. LogServeUri

Specifies location of logs.

Feature	Value
Display Name	LogServeUri
Standard	Custom
Feature type	String
Access	RO
Visibility	Guru
Category	DeviceMaintenance

3. NonUniformityCorrectionControl

3.1. NucMode

Every pixel of the sensor has its own dark level and sensitivity for light.

Bias correction allows to compensate the difference of dark levels between all pixels.

Flat correction allows to compensate the difference of sensitivity levels between all pixels.

They are mainly used when using long exposure durations.

Prior to enabling the corrections, corresponding correction files must be computed or uploaded to the camera.

Selects the non uniformity corrections.

Feature	Value
Display Name	Active corrections
Standard	Custom
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	NonUniformityCorrectionControl

Possible values	Description
None	No correction.
Bias	Bias correction is applied.
BiasFlat	Bias and FLat corrections are applied.

3.2. BuildBiasExecute

Start the generation of a BIAS correction file.

Feature	Value
Display Name	Build bias
Standard	Custom
Feature type	Command
Access	WO
Visibility	Expert
Category	NonUniformityCorrectionControl
Affects	BuildNucStatus BuildNucDuration

Bias can only be computed when NucMode is set to None.

3.3. BuildFlatExecute

Start the generation of a FLAT correction file.

Feature	Value
Display Name	Build flat
Standard	Custom
Feature type	Command
Access	WO
Visibility	Expert
Category	NonUniformityCorrectionControl
Affects	BuildNucStatus BuildNucDuration

Flat can only be computed when NucMode is set to Bias.

3.4. BuildNucNbImages

Number of images used to build the NUC.

Feature	Value
Display Name	Nb Images for NUC computation
Standard	Custom
Feature type	Integer
Access	RW
Visibility	Expert
Category	NonUniformityCorrectionControl
Affects	BuildNucDuration

3.5. BuildNucAbort

Abort the generation.

Feature	Value
Display Name	Abort build
Standard	Custom
Feature type	Command
Access	WO
Visibility	Expert
Category	NonUniformityCorrectionControl
Affects	BuildNucStatus BuildNucDuration

3.6. BuildNucStatusRefresh

Force reload of NUC generation status

Feature	Value
Display Name	Reload NUC status
Standard	Custom
Feature type	Command
Access	WO
Visibility	Expert
Category	NonUniformityCorrectionControl
Affects	BuildNucStatus BuildNucDuration

3.7. BuildNucStatus

Returns NUC computation status.

Feature	Value
Display Name	Build NUC status
Standard	Custom
Feature type	Enumeration
Access	RO
Visibility	Expert
Category	NonUniformityCorrectionControl

Possible values	Description
<i>Idle</i>	No NUC build operation has been requested.
<i>InProgress</i>	NUC build operation is in progress.
<i>Done</i>	NUC build operation completed successfully.
<i>Failed</i>	NUC build operation failed.

3.8. BuildNucDuration

Estimating NUC computation duration.

Feature	Value
Display Name	NUC computation duration
Standard	Custom
Feature type	Integer
Access	RO
Visibility	Expert
Unit	s
Category	NonUniformityCorrectionControl

3.9. AduOffset

Offset applied to all pixels. The offset is added after bias/flat correction and before conversion to final pixel format

Feature	Value
Display Name	ADU offset
Standard	Custom
Feature type	Integer
Access	RW
Visibility	Expert
Category	NonUniformityCorrectionControl

4. ImageProcessingControl

4.1. MedianFilterThresholdEnable

Enables replacement of pixels according to the difference with their median.

Feature	Value
Display Name	Median Filter Threshold Enable
Standard	Custom
Feature type	Boolean
Access	RW
Visibility	Expert
Category	ImageProcessingControl

4.2. MedianFilterThreshold

Threshold used for pixel replacement.

Feature	Value
Display Name	Median Filter Threshold
Standard	Custom
Feature type	Float
Access	RW
Visibility	Expert
Category	ImageProcessingControl

4.3. MedianFilterSaturationEnable

Enables replacement of saturated pixels by their median.

Feature	Value
Display Name	Replaces saturated pixels by their median
Standard	Custom
Feature type	Boolean
Access	RW
Visibility	Expert
Category	ImageProcessingControl

5. DebugEthernet

5.1. CurrentIPAddress

Reports the IP address of the camera Ethernet link.

Feature	Value
Display Name	Ethernet Current IP Address
Standard	Custom
Feature type	String
Access	RO
Visibility	Expert
Category	DebugEthernet

5.2. CurrentSubnetMask

Reports the subnet mask of the camera Ethernet link.

Feature	Value
Display Name	Ethernet Current Subnet Mask
Standard	Custom
Feature type	String
Access	RO
Visibility	Expert
Category	DebugEthernet

5.3. IPMode

Specifies how the camera Ethernet link is configured.

Feature	Value
Display Name	IP Configuration Mode
Standard	Custom
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	DebugEthernet

Possible values	Description
<i>Automatic</i>	Automatic IP configuration using DHCP.
<i>Manual</i>	Manual IP configuration.

5.4. IPReconfigure

Reconfigures Network.

Feature	Value
Display Name	Reconfigures Network.
Standard	Custom
Feature type	Command
Access	WO
Visibility	Expert
Category	DebugEthernet

5.5. StaticIPAddress

Controls the static IP address of the camera ethernet link. It is only used when the DHCP configuration scheme is disabled.

Feature	Value
Display Name	Static IP Address
Standard	Custom
Feature type	String
Access	RW
Visibility	Expert
Category	DebugEthernet

5.6. StaticSubnetMask

Controls the static subnet mask associated with the static IP address of the camera ethernet link. It is only used when the DHCP configuration scheme is disabled.

Feature	Value
Display Name	Static Subnet Mask
Standard	Custom
Feature type	String
Access	RW
Visibility	Expert
Category	DebugEthernet

5.7. StaticDefaultGateway

Controls the static default gateway associated with the static IP address of the camera ethernet link. It is only used when the DHCP configuration scheme is disabled.

Feature	Value
Display Name	Static Default Gateway
Standard	Custom
Feature type	String
Access	RW
Visibility	Expert
Category	DebugEthernet

5.8. StaticDomainNameServer

Controls the static domain name server associated with the static IP address of the camera ethernet link. It is only used when the DHCP configuration scheme is disabled.

Feature	Value
Display Name	Static Domain Name Server
Standard	Custom
Feature type	String
Access	RW
Visibility	Expert
Category	DebugEthernet

5.9. StaticAlternateDomainNameServer

Controls the static alternate domain name server associated with the static IP address of the camera ethernet link. It is only used when the DHCP configuration scheme is disabled.

Feature	Value
Display Name	Static Alternate Domain Name Server
Standard	Custom
Feature type	String
Access	RW
Visibility	Expert
Category	DebugEthernet

5.10. IPRestoreDefault

Restore default network configuration.

Feature	Value
Display Name	Restore default network configuration
Standard	Custom
Feature type	Command
Access	WO
Visibility	Expert
Category	DebugEthernet
Affects	IPMode StaticIPAddress StaticSubnetMask StaticDefaultGateway StaticDomainNameServer StaticAlternateDomainNameServer

6. ImageFormatControl

6.1. SensorWidth

Effective width of the sensor in pixels.

Feature	Value
Display Name	Sensor Width
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RO
Visibility	Expert
Category	ImageFormatControl

6.2. SensorHeight

Effective height of the sensor in pixels.

Feature	Value
Display Name	Sensor Height
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RO
Visibility	Expert
Category	ImageFormatControl

6.3. SensorPixelWidth

Physical size (pitch) in the x direction of a photo sensitive pixel unit.

Feature	Value
Display Name	Sensor Pixel Width
Standard	GeniCam SFNC Version 2.5
Feature type	Float
Access	RO
Visibility	Guru
Unit	µm
Category	ImageFormatControl

6.4. SensorPixelHeight

Physical size (pitch) in the y direction of a photo sensitive pixel unit.

Feature	Value
Display Name	Sensor Pixel Height
Standard	GeniCam SFNC Version 2.5
Feature type	Float
Access	RO
Visibility	Guru
Unit	µm
Category	ImageFormatControl

6.5. SensorName

Product name of the imaging Sensor.

Feature	Value
Display Name	Sensor Name
Standard	GeniCam SFNC Version 2.5
Feature type	String
Access	RO
Visibility	Guru
Category	ImageFormatControl

SensorName varies according to the variant of the camera.

"IMX426LLJ-C" is used for C-BLUE 2 0.5 MP

"IMX425LLJ-C" is used for C-BLUE 2 1.7 MP

"IMX420LLJ-C" is used for C-BLUE 2 7.1 MP

"IMX530-AAMJ-C" is used for C-BLUE 2 24.5 MP

"IMX487-AAMJ-C" is used for C-BLUE 2 UV

6.6. SensorShutterMode

Specifies the shutter mode of the device.

Feature	Value
Display Name	Sensor Shutter Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RO
Visibility	Guru
Category	ImageFormatControl

Possible values	Description
<i>Global</i>	The shutter opens and closes at the same time for all pixels. All the pixels are exposed for the same length of time at the same time.

6.7. WidthMax

Maximum width of the image (in pixels). The dimension is calculated after horizontal binning, decimation or any other function changing the horizontal dimension of the image.

Feature	Value
Display Name	Width Max
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RO
Visibility	Expert
Category	ImageFormatControl

6.8. HeightMax

Maximum height of the image (in pixels). This dimension is calculated after vertical binning, decimation or any other function changing the vertical dimension of the image.

Feature	Value
Display Name	Height Max
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RO
Visibility	Expert
Category	ImageFormatControl

6.9. RegionSelector

Selects the Region of interest to control. The RegionSelector feature allows devices that are able to extract multiple regions out of an image, to configure the features of those individual regions independently.

Feature	Value
Display Name	Region Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Beginner
Category	ImageFormatControl
Selects	RegionDestination Width Height OffsetX OffsetY Sparse SparseSelector SparseOffsetX SparseWidth SparseOffsetY SparseHeight

Possible values	Description
<i>Region0</i>	Selected feature will control the region 0.

6.10. RegionMode

Controls if the selected Region of interest is active and streaming.

Feature	Value
Display Name	Region Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RO
Locked	During acquisition
Visibility	Beginner
Category	ImageFormatControl

Possible values	Description
<i>On</i>	Enable the usage of the Region.

6.11. RegionDestination[RegionSelector]

Controls the destination of the selected region.

Feature	Value
Display Name	Region Destination
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl

Possible values	Description
<i>Stream0</i>	The destination of the region is the data stream 0.

6.12. Width[RegionSelector]

Width of the image provided by the device (in pixels).

Feature	Value
Display Name	Width
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	ImageFormatControl
Affects	AcquisitionLineDelay PayloadSize AcquisitionFrameRate MaximumExternalAcquisitionFrameRate ExposureTime MinimumExternalExposureTime

6.13. Height[RegionSelector]

Height of the image provided by the device (in pixels).

Feature	Value
Display Name	Height
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	ImageFormatControl
Affects	AcquisitionLineDelay PayloadSize AcquisitionFrameRate MaximumExternalAcquisitionFrameRate ExposureTime MinimumExternalExposureTime

6.14. OffsetX[RegionSelector]

Horizontal offset from the origin to the region of interest (in pixels).

Feature	Value
Display Name	Offset X
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	ImageFormatControl

6.15. OffsetY[RegionSelector]

Vertical offset from the origin to the region of interest (in pixels).

Feature	Value
Display Name	Offset Y
Standard	GenICam SFNC Version 2.5
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	ImageFormatControl

6.16. Sparse[RegionSelector]

Controls whether the region is contiguous or split in different areas.

Feature	Value
Display Name	Sparse
Standard	Custom
Feature type	Boolean
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl
Affects	Width Height OffsetX OffsetY SparseWidth SparseHeight SparseOffsetX SparseOffsetY SparseMode AcquisitionLineDelay PayloadSize AcquisitionFrameRate MaximumExternalAcquisitionFrameRate ExposureTime MinimumExternalExposureTime

6.17. SparseSelector[RegionSelector]

Selects the sparse area to be configured.

Feature	Value
Display Name	Sparse Area Selector
Standard	Custom
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	ImageFormatControl
Selects	SparseWidth SparseHeight SparseOffsetX SparseOffsetY SparseMode

Possible values	Description
<i>Region0</i>	Selected feature will control the sparse region 0.
<i>Region1</i>	Selected feature will control the sparse region 1.
<i>Region2</i>	Selected feature will control the sparse region 2.
<i>Region3</i>	Selected feature will control the sparse region 3.
<i>Region4</i>	Selected feature will control the sparse region 4.
<i>Region5</i>	Selected feature will control the sparse region 5.
<i>Region6</i>	Selected feature will control the sparse region 6.
<i>Region7</i>	Selected feature will control the sparse region 7.

6.18. SparseWidth[RegionSelector][SparseSelector]

Width of the sparse area (in pixels).

Feature	Value
Display Name	Sparse area Width
Standard	Custom
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl
Affects	Width AcquisitionLineDelay PayloadSize AcquisitionFrameRate MaximumExternalAcquisitionFrameRate ExposureTime MinimumExternalExposureTime

6.19. SparseHeight[RegionSelector][SparseSelector]

Height of the sparse area (in pixels).

Feature	Value
Display Name	Sparse area Height
Standard	Custom
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl
Affects	Height AcquisitionLineDelay PayloadSize AcquisitionFrameRate MaximumExternalAcquisitionFrameRate ExposureTime MinimumExternalExposureTime

6.20. SparseOffsetX[RegionSelector][SparseSelector]

Horizontal offset from the origin to the sparse area (in pixels).

Feature	Value
Display Name	Sparse area Offset X
Standard	Custom
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl
Affects	OffsetX

6.21. SparseOffsetY[RegionSelector][SparseSelector]

Vertical offset from the origin to the sparse area (in pixels).

Feature	Value
Display Name	Sparse area Offset Y
Standard	Custom
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl
Affects	OffsetY

6.22. SparseMode[SparseSelector]

Controls if the selected sparse area is active.

Feature	Value
Display Name	Sparse Region Mode
Standard	Custom
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl
Affects	Width Height OffsetX OffsetY AcquisitionLineDelay PayloadSize AcquisitionFrameRate MaximumExternalAcquisitionFrameRate ExposureTime MinimumExternalExposureTime

Possible values	Description
<i>Off</i>	Disable the usage of the sparse area.
<i>On</i>	Enable the usage of the sparse area.

6.23. BinningSelector

Selects which binning engine is controlled by the BinningHorizontal and BinningVertical features.

Feature	Value
Display Name	Binning Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RO
Visibility	Expert
Category	ImageFormatControl
Selects	BinningHorizontalMode BinningHorizontal BinningVerticalMode BinningVertical

Possible values	Description
<i>Sensor</i>	Selected features will control the sensor binning.

Depending on the camera model and current pixel format, binning feature may or may not be available.

C-BLUE 2 7.1 MP camera supports binning in all pixel formats.

C-BLUE 2 UV camera supports binning in 8, 10 and 12 bits formats only (no HDR).

C-BLUE 2 24.5 MP camera supports binning in 8, 10 and 12 bits formats only (no HDR).

Other cameras do not support binning

6.24. BinningHorizontalMode[BinningSelector]

Sets the mode to use to combine horizontal photo-sensitive cells together when BinningHorizontal is used.

Feature	Value
Display Name	Binning Horizontal Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl
Affects	BinningVerticalMode

Possible values	Description
Sum	The response from the combined cells will be added, resulting in increased sensitivity.
Average	The response from the combined cells will be averaged, resulting in increased signal/noise ratio.

Average is only valid for C-BLUE 2 7.1 MP camera.

All other cameras support only Sum mode.

6.25. BinningHorizontal[BinningSelector]

Number of horizontal photo-sensitive cells to combine together. This reduces the horizontal resolution (width) of the image.

Feature	Value
Display Name	Binning Horizontal
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl
Affects	WidthMax HeightMax Width Height OffsetX OffsetY Sparse SparseWidth SparseHeight SparseOffsetX SparseOffsetY SparseMode BinningVertical PayloadSize AcquisitionFrameRate MaximumExternalAcquisitionFrameRate ExposureTime MinimumExternalExposureTime

6.26. BinningVerticalMode[BinningSelector]

Sets the mode to use to combine vertical photo-sensitive cells together when BinningVertical is used.

Feature	Value
Display Name	Binning Vertical Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl
Affects	BinningHorizontalMode

Possible values	Description
Sum	The response from the combined cells will be added, resulting in increased sensitivity.
Average	The response from the combined cells will be averaged, resulting in increased signal/noise ratio.

The only supported BinningVerticalMode supported is Sum.

6.27. BinningVertical[BinningSelector]

Number of vertical photo-sensitive cells to combine together. This reduces the vertical resolution (height) of the image.

Feature	Value
Display Name	Binning Vertical
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Expert
Category	ImageFormatControl
Affects	WidthMax HeightMax Width Height OffsetX OffsetY Sparse SparseWidth SparseHeight SparseOffsetX SparseOffsetY SparseMode BinningHorizontal PayloadSize AcquisitionFrameRate MaximumExternalAcquisitionFrameRate ExposureTime MinimumExternalExposureTime

6.28. ReverseX

Flip horizontally the image sent by the device. The Region of interest is applied after the flipping.

Feature	Value
Display Name	Reverse X
Standard	GeniCam SFNC Version 2.5
Feature type	Boolean
Access	RW
Visibility	Expert
Category	ImageFormatControl

6.29. ReverseY

Flip vertically the image sent by the device. The Region of interest is applied after the flipping.

Feature	Value
Display Name	Reverse Y
Standard	GeniCam SFNC Version 2.5
Feature type	Boolean
Access	RW
Visibility	Expert
Category	ImageFormatControl

6.30. PixelFormat

Format of the pixels provided by the device. It represents all the information provided by PixelSize, PixelColorFilter combined in a single feature.

Feature	Value
Display Name	Pixel Format
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	ImageFormatControl
Affects	AduOffset Width Height OffsetX OffsetY Sparse SparseWidth SparseHeight SparseOffsetX SparseOffsetY SparseMode BinningHorizontal BinningVertical ReverseX ReverseY HDRMode TestPattern AcquisitionFramerateAvailable AcquisitionLineDelay GlowReduction

BlackLevelAuto
ConversionEfficiency
PayloadSize
AcquisitionFrameRate
MaximumExternalAcquisitionFrameRate
ExposureTime
MinimumExternalExposureTime
Gain
BlackLevel

Possible values	Description
Mono8	Monochrome 8-bit
Mono10	Monochrome 10-bit unpacked
Mono12	Monochrome 12-bit unpacked
Mono14	Monochrome 14-bit unpacked
Mono16	Monochrome 16-bit

The list of the possible values in the table is common to all C-BLUE cameras.

The actual list depends on the camera variant.

Mono8, Mono10 and Mono12 are available on all C-BLUE cameras.

Mono14 is available only on C-BLUE 2 0.5 MP, C-BLUE 2 1.7 MP and C-BLUE 2 7.1 MP cameras.

Mono16 is available only on C-BLUE 2 UV and C-BLUE 2 24.5 MP camera.

6.31. HDRMode

Select the HDR computation mode. This field is only available if HDR is enabled, e.g PixelFormat is set to Mono14 or Mono16.

Feature	Value
Display Name	HDR Mode
Standard	Custom
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Guru
Category	ImageFormatControl
Affects	AduOffset WidthMax HeightMax Width Height OffsetX OffsetY Sparse SparseWidth SparseHeight SparseOffsetX SparseOffsetY SparseMode

Possible values	Description
<i>Standard</i>	Composite image is done using high and low gain images
<i>Low</i>	Composite image contains the image corresponding to the low gain.
<i>High</i>	Composite image contains the image corresponding to the high gain.
<i>Raw</i>	The image contains lines alternatively corresponding to low and high gain

6.32. TestPattern

Selects the type of test pattern that is generated by the device as image source.

Feature	Value
Display Name	Test Pattern
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	ImageFormatControl

Possible values	Description
<i>Off</i>	Image is coming from the sensor.
<i>Black</i>	Image is filled with the darkest possible image.
<i>White</i>	Image is filled with the brightest possible image.
<i>GreyHorizontalRamp</i>	Image is filled horizontally with an image that goes from the darkest possible value to the brightest.
<i>SimulatorGreyHorizontalRamp</i>	Image is filled horizontally with an image that goes from the darkest possible value to the brightest.
<i>SimulatorGreyHorizontalRampMoving</i>	Image is filled horizontally with an image that goes from the darkest possible value to the brightest and that moves horizontally from left to right at each frame.

7. AcquisitionControl

7.1. AcquisitionMode

Sets the acquisition mode of the device. It defines mainly the number of frames to capture during an acquisition and the way the acquisition stops.

Feature	Value
Display Name	Acquisition Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	AcquisitionControl

Possible values	Description
Continuous	Frames are captured continuously until stopped with the AcquisitionStop command.

7.2. AcquisitionStart

Starts the Acquisition of the device. The number of frames captured is specified by AcquisitionMode.

Feature	Value
Display Name	Acquisition Start
Standard	GeniCam SFNC Version 2.5
Feature type	Command
Access	RW
Visibility	Beginner
Category	AcquisitionControl
Affects	AcquisitionFramerateAvailable ExposureTimeAvailable AcquisitionStarted

7.3. AcquisitionStop

Stops the Acquisition of the device at the end of the current Frame. It is mainly used when AcquisitionMode is Continuous but can be used in any acquisition mode.

Feature	Value
Display Name	Acquisition Stop
Standard	GeniCam SFNC Version 2.5
Feature type	Command
Access	RW
Visibility	Beginner
Category	AcquisitionControl
Affects	AcquisitionFramerateAvailable ExposureTimeAvailable AcquisitionStarted

7.4. AcquisitionStarted

Checks if an acquisition has been started.

Feature	Value
Display Name	Acquisition started
Standard	Custom
Feature type	Boolean
Access	RO
Visibility	Beginner
Category	AcquisitionControl

7.5. AcquisitionAbort

Aborts the Acquisition immediately. This will end the capture without completing the current Frame or waiting on a trigger. If no Acquisition is in progress, the command is ignored.

Feature	Value
Display Name	Acquisition Abort
Standard	GeniCam SFNC Version 2.5
Feature type	Command
Access	RW
Visibility	Expert
Category	AcquisitionControl
Affects	AcquisitionStarted

7.6. AcquisitionBurstFrameCount

Number of frames to acquire for each FrameBurstStart trigger.

Feature	Value
Display Name	Acquisition Burst Frame Count
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	AcquisitionControl

7.7. AcquisitionFrameRate

Controls the acquisition rate (in Hertz) at which the frames are captured.

Feature	Value
Display Name	Acquisition Frame Rate
Standard	GeniCam SFNC Version 2.5
Feature type	Float
Access	RW
Locked	During acquisition
Visibility	Beginner
Unit	Hz
Category	AcquisitionControl
Affects	ExposureTime MinimumExternalExposureTime

7.8. MaximumExternalAcquisitionFrameRate

Tells the maximum external acquisition rate (in Hertz) at which the frames can be triggered.

Feature	Value
Display Name	Maximum External Acquisition Frame Rate
Standard	Custom
Feature type	Float
Access	RO
Visibility	Beginner
Unit	Hz
Category	AcquisitionControl

7.9. AcquisitionLineDelay

Extra delay between the acquisition of two lines. This impacts the maximum framerate and exposure granularity

Feature	Value
Display Name	Acquisition Line Delay
Standard	Custom
Feature type	Integer
Access	RW
Visibility	Guru
Category	AcquisitionControl
Affects	PayloadSize AcquisitionFrameRate MaximumExternalAcquisitionFrameRate

7.10. TriggerSelector

Selects the type of trigger to configure.

Feature	Value
Display Name	Trigger Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Beginner
Category	AcquisitionControl
Selects	TriggerMode TriggerSoftware TriggerSource TriggerActivation TriggerOverlap TriggerDelay

Possible values	Description
AcquisitionStart	Selects a trigger that starts the Acquisition of one or many frames according to AcquisitionMode.
AcquisitionEnd	Selects a trigger that ends the Acquisition of one or many frames according to AcquisitionMode.
FrameStart	Selects a trigger starting the capture of one frame.

FrameBurstStart	Selects a trigger starting the capture of the bursts of frames in an acquisition. AcquisitionBurstFrameCount controls the length of each burst unless a FrameBurstEnd trigger is active. The total number of frames captured is also conditioned by AcquisitionFrameCount if AcquisitionMode is MultiFrame.
FrameBurstEnd	Selects a trigger ending the capture of the bursts of frames in an acquisition.
ExposureStart	Selects a trigger controlling the start of the exposure of one Frame (or Line).
ExposureEnd	Selects a trigger controlling the end of the exposure of one Frame (or Line).

7.11. TriggerMode[TriggerSelector]

Controls if the selected trigger is active.

Feature	Value
Display Name	Trigger Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	AcquisitionControl
Affects	AcquisitionFramerateAvailable ExposureTimeAvailable ExposureMode PayloadSize AcquisitionFrameRate MaximumExternalAcquisitionFrameRate ExposureTime MinimumExternalExposureTime

Possible values	Description
Off	Disables the selected trigger.
On	Enable the selected trigger.

7.12. TriggerSoftware[TriggerSelector]

Generates an internal trigger. TriggerSource must be set to Software.

Feature	Value
Display Name	Trigger Software
Standard	GeniCam SFNC Version 2.5
Feature type	Command
Access	WO
Visibility	Beginner
Category	AcquisitionControl

7.13. TriggerSource[TriggerSelector]

Specifies the internal signal or physical input Line to use as the trigger source. The selected trigger must have its TriggerMode set to On.

Feature	Value
Display Name	Trigger Source
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	AcquisitionControl

Possible values	Description
Software	Specifies that the trigger source will be generated by software using the TriggerSoftware command.
Line0	Specifies which physical line (or pin) and associated I/O control block to use as external source for the trigger signal.
Line1	Specifies which physical line (or pin) and associated I/O control block to use as external source for the trigger signal.
LinkTrigger0	Specifies which Link Trigger to use as source for the trigger (received from the transport layer).

7.14. TriggerActivation[TriggerSelector]

Specifies the activation mode of the trigger.

Feature	Value
Display Name	Trigger Activation
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	AcquisitionControl

Possible values	Description
RisingEdge	Specifies that the trigger is considered valid on the rising edge of the source signal.
FallingEdge	Specifies that the trigger is considered valid on the falling edge of the source signal.

7.15. TriggerOverlap[TriggerSelector]

Specifies the type trigger overlap permitted with the previous frame or line. This defines when a valid trigger will be accepted (or latched) for a new frame or a new line.

Feature	Value
Display Name	Trigger Overlap
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Expert
Category	AcquisitionControl

Possible values	Description
<i>Off</i>	No trigger overlap is permitted.

7.16. TriggerDelay[TriggerSelector]

Specifies the delay in microseconds (us) to apply after the trigger reception before activating it.

Feature	Value
Display Name	Trigger Delay
Standard	GeniCam SFNC Version 2.5
Feature type	Float
Access	RW
Locked	During acquisition
Visibility	Expert
Unit	us
Category	AcquisitionControl

7.17. ExposureMode

Sets the operation mode of the Exposure.

Feature	Value
Display Name	Exposure Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	AcquisitionControl
Affects	TriggerMode

Possible values	Description
<i>Timed</i>	Timed exposure. The exposure duration time is set using the ExposureTime features and the exposure starts with the FrameStart.
<i>TriggerControlled</i>	Uses one or more trigger signal(s) to control the exposure duration. See ExposureStart, ExposureEnd of the TriggerSelector feature.

7.18. ExposureTime

Sets the Exposure time when ExposureMode is Timed and ExposureAuto is Off. This controls the duration where the photosensitive cells are exposed to light.

Feature	Value
Display Name	Exposure Time
Standard	GeniCam SFNC Version 2.5
Feature type	Float
Access	RW
Locked	During acquisition
Visibility	Beginner
Unit	us
Category	AcquisitionControl
Affects	AcquisitionFrameRate

7.19. MinimumExternalExposureTime

Tells the Minimum External Exposure time when ExposureMode is Timed, ExposureAuto is Off and Exposure Start/End triggers are enabled.

Feature	Value
Display Name	Minimal External Exposure Time
Standard	Custom
Feature type	Float
Access	RO
Visibility	Beginner
Unit	us
Category	AcquisitionControl

7.20. GlowReduction

Controls the glow reduction scheme in use.

Feature	Value
Display Name	Glow Reduction
Standard	Custom
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Expert
Category	AcquisitionControl

Possible values	Description
Off	No glow reduction is applied.
On	Glow reduction is applied.

Glow reduction is only available on C-BLUE 2 0.5 MP, C-BLUE 2 1.7 MP and C-BLUE 2 7.1 MP cameras.

8. AnalogControl

8.1. GainSelector

Selects which Gain is controlled by the various Gain features.

Feature	Value
Display Name	Gain Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Beginner
Category	AnalogControl
Selects	Gain

Possible values	Description
AnalogAll	Gain will be applied to all analog channels or taps.
DigitalAll	Gain will be applied to all digital channels or taps.

8.2. Gain[GainSelector]

Controls the selected gain as an absolute physical value. This is an amplification factor applied to the video signal.

Feature	Value
Display Name	Gain
Standard	GeniCam SFNC Version 2.5
Feature type	Float
Access	RW
Locked	During acquisition
Visibility	Beginner
Unit	dB
Category	AnalogControl

8.3. BlackLevelSelector

Selects which Black Level is controlled by the various Black Level features.

Feature	Value
Display Name	Black Level Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	AnalogControl
Selects	BlackLevel BlackLevelAuto

Possible values	Description
All	Black Level will be applied to all channels or taps.

8.4. BlackLevel[BlackLevelSelector]

Controls the analog black level as an absolute physical value. This represents a DC offset applied to the video signal.

Feature	Value
Display Name	Black Level
Standard	GeniCam SFNC Version 2.5
Feature type	Float
Access	RW
Locked	During acquisition
Visibility	Expert
Category	AnalogControl

8.5. BlackLevelAuto[BlackLevelSelector]

Controls the mode for automatic black level adjustment. The exact algorithm used to implement this adjustment is device-specific.

Feature	Value
Display Name	Black Level Auto
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Expert
Category	AnalogControl

Possible values	Description
<i>Off</i>	Analog black level is user controlled using BlackLevel.
<i>Continuous</i>	Analog black level is constantly adjusted by the device.

8.6. ConversionEfficiency

Controls the conversion efficiency.

Feature	Value
Display Name	Conversion Efficiency
Standard	Custom
Feature type	Enumeration
Access	RW
Locked	During acquisition
Visibility	Beginner
Category	AnalogControl

Possible values	Description
<i>Low</i>	The selected conversion efficiency is low.
<i>High</i>	The selected conversion efficiency is high.

ConversionEfficiency is only available on C-BLUE 2 0.5 MP, C-BLUE 2 1.7 MP and C-BLUE 2 7.1 MP cameras.

9. DigitalIOControl

9.1. LineSelector

Selects the physical line (or pin) of the external device connector or the virtual line of the Transport Layer to configure.

Feature	Value
Display Name	Line Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	DigitalIOControl
Selects	LineMode LineSource

Possible values	Description
<i>Line2</i>	Pin #2 of the I/O connector.
<i>Line3</i>	Pin #3 of the I/O connector.

9.2. LineMode[LineSelector]

Controls if the physical Line is used to Input or Output a signal.

Feature	Value
Display Name	Line Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RO
Visibility	Expert
Category	DigitalIOControl

Possible values	Description
<i>Input</i>	The selected physical line is used to Input an electrical signal.
<i>Output</i>	The selected physical line is used to Output an electrical signal.

9.3. LineSource[LineSelector]

Selects which internal acquisition or I/O source signal to output on the selected Line. LineMode must be Output.

Feature	Value
Display Name	Line Source
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	DigitalIOControl

Possible values	Description
ExposureActive	Device is doing the exposure of a Frame (or Line).
SensorReadout	Readout of the sensor is in progress.
SensorClock	Clock sent to the sensor. Frequency is 74.25 MHz.

10. UserSetControl

10.1. UserSetSelector

Selects the feature User Set to load, save or configure.

Feature	Value
Display Name	User Set Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Beginner
Category	UserSetControl

Possible values	Description
Default8bits	Selects the 8 bits low sensitivity factory setting user set.
Default10bits	Selects the 10 bits low sensitivity factory setting user set.
Default12bits	Selects the 12 bits low sensitivity factory setting user set.
HighSensitivity8bits	Selects the 8 bits high sensitivity factory setting user set.
HighSensitivity10bits	Selects the 10 bits high sensitivity factory setting user set.
HighSensitivity12bits	Selects the 12 bits high sensitivity factory setting user set.
UserSet0	Selects the user set 0.
UserSet1	Selects the user set 1.
UserSet2	Selects the user set 2.
UserSet3	Selects the user set 3.
UserSet4	Selects the user set 4.
UserSet5	Selects the user set 5.
UserSet6	Selects the user set 6.
UserSet7	Selects the user set 7.
UserSet8	Selects the user set 8.
UserSet9	Selects the user set 9.

10.2. UserSetLoad

Loads the User Set specified by UserSetSelector to the device and makes it active.

Feature	Value
Display Name	User Set Load
Standard	GeniCam SFNC Version 2.5
Feature type	Command
Access	RW
Visibility	Beginner
Category	UserSetControl

10.3. UserSetSave

Save the User Set specified by UserSetSelector to the non-volatile memory of the device.

Feature	Value
Display Name	User Set Save
Standard	GeniCam SFNC Version 2.5
Feature type	Command
Access	RW
Visibility	Beginner
Category	UserSetControl

10.4. UserSetDefault

Selects the feature User Set to load and make active by default when the device is reset.

Feature	Value
Display Name	User Set Default
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Beginner
Category	UserSetControl

Possible values	Description
<i>Default8bits</i>	Selects the 8 bits low sensitivity factory setting user set.
<i>Default10bits</i>	Selects the 10 bits low sensitivity factory setting user set.
<i>Default12bits</i>	Selects the 12 bits low sensitivity factory setting user set.
<i>HighSensitivity8bits</i>	Selects the 8 bits high sensitivity factory setting user set.
<i>HighSensitivity10bits</i>	Selects the 10 bits high sensitivity factory setting user set.
<i>HighSensitivity12bits</i>	Selects the 12 bits high sensitivity factory setting user set.
<i>UserSet0</i>	Selects the user set 0.
<i>UserSet1</i>	Select the user set 1.
<i>UserSet2</i>	Select the user set 2.
<i>UserSet3</i>	Select the user set 3.
<i>UserSet4</i>	Select the user set 4.
<i>UserSet5</i>	Select the user set 5.
<i>UserSet6</i>	Select the user set 6.

<i>UserSet7</i>	Select the user set 7.
<i>UserSet8</i>	Select the user set 8.
<i>UserSet9</i>	Select the user set 9.

11. FileAccessControl

11.1. FileSelector

Selects the target file in the device.

Feature	Value
Display Name	File Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Guru
Category	FileAccessControl
Selects	FileOperationSelector FileOpenMode FileSize

Possible values	Description
<i>Bias</i>	The bias correction.
<i>Flat</i>	The flat correction
<i>Firmware</i>	The firmware the device.

11.2. FileOperationSelector[FileSelector]

Selects the target operation for the selected file in the device. This Operation is executed when the FileOperationExecute feature is called.

Feature	Value
Display Name	File Operation Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Guru
Category	FileAccessControl
Selects	FileOperationExecute FileAccessOffset FileAccessLength FileOperationStatus FileOperationResult

Possible values	Description
Open	Opens the file selected by FileSelector in the device. The access mode in which the file is opened is selected by FileMode.
Close	Closes the file selected by FileSelector in the device.
Read	Reads FileAccessLength bytes from the device storage at the file relative offset FileAccessOffset into FileAccessBuffer.
Write	Writes FileAccessLength bytes taken from the FileAccessBuffer into the device storage at the file relative offset FileAccessOffset.
Delete	Deletes the file selected by FileSelector in the device. Note that deleting a device file should not remove the associated FileSelector entry to allow future operation on this file.

11.3. FileOperationExecute[FileOperationSelector]

Executes the operation selected by FileOperationSelector on the selected file.

Feature	Value
Display Name	File Operation Execute
Standard	GeniCam SFNC Version 2.5
Feature type	Command
Access	WO
Visibility	Guru
Category	FileAccessControl
Affects	FileAccessOffset FileOperationStatus FileOperationResult

11.4. FileMode[FileSelector]

Selects the access mode in which a file is opened in the device.

Feature	Value
Display Name	File Open Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Guru
Category	FileAccessControl

Possible values	Description
Read	This mode selects read-only open mode.
Write	This mode selects write-only open mode.

11.5. FileAccessOffset[FileOperationSelector]

Controls the Offset of the mapping between the device file storage and the FileAccessBuffer.

Feature	Value
Display Name	File Access Offset
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Visibility	Guru
Unit	B
Category	FileAccessControl

11.6. FileAccessLength[FileOperationSelector]

Controls the Length of the mapping between the device file storage and the FileAccessBuffer.

Feature	Value
Display Name	File Access Length
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Visibility	Guru
Unit	B
Category	FileAccessControl

11.7. FileOperationStatus[FileOperationSelector]

Represents the file operation execution status.

Feature	Value
Display Name	File Operation Status
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RO
Visibility	Guru
Category	FileAccessControl

Possible values	Description
Success	File Operation was successful.
Failure	File Operation failed.

11.8. FileOperationResult[FileOperationSelector]

Represents the file operation result. For Read or Write operations, the number of successfully read/written bytes is returned.

Feature	Value
Display Name	File Operation Result
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RO
Visibility	Guru
Category	FileAccessControl

11.9. FileSize[FileSelector]

Represents the size of the selected file in bytes.

Feature	Value
Display Name	File Size
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RO
Visibility	Guru
Unit	B
Category	FileAccessControl

12. TransportLayerControl

12.1. TLParamsLocked

Used by the Transport Layer to prevent critical features from changing during acquisition.

Feature	Value
Display Name	TL Params Locked
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Visibility	Invisible
Category	TransportLayerControl

12.2. PayloadSize

Provides the number of bytes transferred for each data buffer or chunk on the stream channel. This includes any end-of-line, end-of-frame statistics or other stamp data. This is the total size of data payload for a data block.

Feature	Value
Display Name	Payload Size
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RO
Visibility	Expert
Unit	B
Category	TransportLayerControl

13. CoaXPress

13.1. CxpLinkConfigurationStatus

This feature indicates the current and active Link configuration used by the Device.

Feature	Value
Display Name	Cxp Link Configuration Status
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RO
Visibility	Beginner
Category	CoaXPress

Possible values	Description
<i>None</i>	The Link configuration of the Device is unknown. Either the configuration operation has failed or there is nothing connected.
<i>Pending</i>	The Device is in the process of configuring the Link. The Link cannot be used yet.
<i>CXP3_X1</i>	1 Connection operating at CXP-3 speed (3.125 Gbps).
<i>CXP6_X1</i>	1 Connection operating at CXP-6 speed (6.25 Gbps).
<i>CXP10_X1</i>	1 Connection operating at CXP-10 speed (10.00 Gbps).
<i>CXP12_X1</i>	1 Connection operating at CXP-12 speed (12.50 Gbps).
<i>CXP3_X2</i>	2 Connections operating at CXP-3 speed (3.125 Gbps).
<i>CXP6_X2</i>	2 Connections operating at CXP-6 speed (6.25 Gbps).
<i>CXP10_X2</i>	2 Connections operating at CXP-10 speed (10.00 Gbps).
<i>CXP12_X2</i>	2 Connections operating at CXP-12 speed (12.50 Gbps).
<i>CXP3_X4</i>	4 Connections operating at CXP-3 speed (3.125 Gbps).
<i>CXP6_X4</i>	4 Connections operating at CXP-6 speed (6.25 Gbps).
<i>CXP10_X4</i>	4 Connections operating at CXP-10 speed (10.00 Gbps).
<i>CXP12_X4</i>	4 Connections operating at CXP-12 speed (12.50 Gbps).

13.2. CxpLinkConfigurationPreferred

Provides the Link configuration that allows the Transmitter Device to operate in its default mode.

Feature	Value
Display Name	Cxp Link Configuration Preferred
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RO
Visibility	Expert
Category	CoaXPress

Possible values	Description
<i>CXP3_X1</i>	1 Connection operating at CXP-3 speed (3.125 Gbps).
<i>CXP6_X1</i>	1 Connection operating at CXP-6 speed (6.25 Gbps).
<i>CXP10_X1</i>	1 Connection operating at CXP-10 speed (10.00 Gbps).
<i>CXP12_X1</i>	1 Connection operating at CXP-12 speed (12.50 Gbps).
<i>CXP3_X2</i>	2 Connections operating at CXP-3 speed (3.125 Gbps).
<i>CXP6_X2</i>	2 Connections operating at CXP-6 speed (6.25 Gbps).
<i>CXP10_X2</i>	2 Connections operating at CXP-10 speed (10.00 Gbps).
<i>CXP12_X2</i>	2 Connections operating at CXP-12 speed (12.50 Gbps).
<i>CXP3_X4</i>	4 Connections operating at CXP-3 speed (3.125 Gbps).
<i>CXP6_X4</i>	4 Connections operating at CXP-6 speed (6.25 Gbps).
<i>CXP10_X4</i>	4 Connections operating at CXP-10 speed (10.00 Gbps).
<i>CXP12_X4</i>	4 Connections operating at CXP-12 speed (12.50 Gbps).

13.3. CxpLinkConfiguration

This feature allows specifying the Link configuration for the communication between the Receiver and Transmitter Device. In most cases this feature does not need to be written because automatic discovery will set configuration correctly to the value returned by CxpLinkConfigurationPreferred. Note that the currently active configuration of the Link can be read using CxpLinkConfigurationStatus.

Feature	Value
Display Name	Cxp Link Configuration
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Beginner
Category	CoaXPress
Affects	CxpLinkConfigurationStatus AcquisitionFrameRate MaximumExternalAcquisitionFrameRate

Possible values	Description
CXP3_X1	1 Connection operating at CXP-3 speed (3.125 Gbps).
CXP6_X1	1 Connection operating at CXP-6 speed (6.25 Gbps).
CXP10_X1	1 Connection operating at CXP-10 speed (10.00 Gbps).
CXP12_X1	1 Connection operating at CXP-12 speed (12.50 Gbps).
CXP3_X2	2 Connections operating at CXP-3 speed (3.125 Gbps).
CXP6_X2	2 Connections operating at CXP-6 speed (6.25 Gbps).
CXP10_X2	2 Connections operating at CXP-10 speed (10.00 Gbps).
CXP12_X2	2 Connections operating at CXP-12 speed (12.50 Gbps).
CXP3_X4	4 Connections operating at CXP-3 speed (3.125 Gbps).
CXP6_X4	4 Connections operating at CXP-6 speed (6.25 Gbps).
CXP10_X4	4 Connections operating at CXP-10 speed (10.00 Gbps).
CXP12_X4	4 Connections operating at CXP-12 speed (12.50 Gbps).

13.4. CxpConnectionSelector

Selects the CoaXPress physical connection to control.

Feature	Value
Display Name	Cxp Connection Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Visibility	Expert
Category	CoaXPress
Selects	CxpConnectionTestMode CxpConnectionTestErrorCount

13.5. CxpConnectionTestMode[CxpConnectionSelectorReg]

Enables the test mode for an individual physical connection of the Device.

Feature	Value
Display Name	Cxp Connection Test Mode
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	CoaXPress

Possible values	Description
Off	Off
Mode1	Mode 1

13.6. CxpConnectionTestErrorCount[CxpConnectionSelectorReg]

Reports the current connection error count for test packets received by the device on the connection selected by CxpConnectionSelector.

Feature	Value
Display Name	Cxp Connection Test Error Count
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Visibility	Expert
Category	CoaXPress

13.7. CxpSendReceiveSelector

Selects which one of the send or receive features to control.

Feature	Value
Display Name	Cxp Send Receive Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	CoaXPress
Selects	CxpConnectionTestPacketCount
Affects	CxpErrorCounterValue CxpErrorCounterStatus

Possible values	Description
Send	Send
Receive	Receive

13.8. CxpConnectionTestPacketCount[CxpSendReceiveSelector]

Reports the current count for the test packets on the connection selected by CxpConnectionSelector.

Feature	Value
Display Name	Cxp Connection Test Packet Count
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Visibility	Expert
Category	CoaXPress

13.9. CxpErrorCounterSelector

Selects which Cxp Error Counter to read or reset.

Feature	Value
Display Name	Cxp Error Counter Selector
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RW
Visibility	Expert
Category	CoaXPress
Selects	CxpErrorCounterReset CxpErrorCounterValue CxpErrorCounterStatus

Possible values	Description
<i>ConnectionLockLoss</i>	Counts the number of times the lock was lost.
<i>Encoding</i>	Counts the number of protocol encoding errors detected.
<i>StreamDataPacketCrc</i>	Counts the number of CRC errors detected in a data packet. This counter is only available on the CoaXpress host.
<i>ControlPacketCrc</i>	Counts the number of CRC errors detected in a control packet.
<i>EventPacketCrc</i>	Counts the number of CRC errors detected in an event packet.
<i>DuplicatedCharactersCorrected</i>	Counts the number of corrected errors in the duplicated characters in CXP control words.
<i>DuplicatedCharactersUncorrected</i>	Counts the number of uncorrected errors in the duplicated characters in CXP control words.

13.10. CxpErrorCounterReset[CxpErrorCounterSelector]

Resets the selected Cxp Error Counter on the connection selected by CxpConnectionSelector. The counter starts counting events immediately after the reset.

Feature	Value
Display Name	Cxp Error Counter Reset
Standard	GeniCam SFNC Version 2.5
Feature type	Command
Access	RW
Visibility	Expert
Category	CoaXPress

13.11. CxpErrorCounterValue[CxpErrorCounterSelector]

Reads the current value of the selected Cxp Error Counter on the connection selected by CxpConnectionSelector.

Feature	Value
Display Name	Cxp Error Counter Value
Standard	GeniCam SFNC Version 2.5
Feature type	Integer
Access	RW
Visibility	Expert
Category	CoaXPress

13.12. CxpErrorCounterStatus[CxpErrorCounterSelector]

Returns the current status of the selected Cxp Error Counter on the connection selected by CxpConnectionSelector.

Feature	Value
Display Name	Cxp Error Counter Status
Standard	GeniCam SFNC Version 2.5
Feature type	Enumeration
Access	RO
Visibility	Expert
Category	CoaXPress

Possible values	Description
<i>CounterActive</i>	The counter is actively counting errors.
<i>CounterOverflow</i>	The counter exceeded its maximum error count.